

SKYTEC SKYTEC ECO COPPER™

LIGHTWEIGHT SOLVENT FREE LATEX GRIP GLOVE WITH RECYCLED POLYESTER **LINER**

Unique patterned latex grip glove with 90% rPET liner offering outstanding grip properties in dry and wet conditions.

FEATURES

- ➤ Lightweight 90% rPET liner (90%) maintains a super thin 'feel' for improved dexterity, fit and comfort
- > Special suction cups pattern which leads to an excellent wet and dry grip
- > Solvent free latex coating which makes it more Eco friendly compared to a crinkle latex glove
- > 19g of CO2 reduced vs an equivalent crinkle latex glove with Nylon liner.
- > RCS (Recycled claim Standard) certified
- > Anatomically designed for high levels of comfort and tactile touch
- ➤ Contact heat protection up to 100°C for a short period (15 sec max)
- > Elasticated wrist provides a secure fit









SUITABLE FOR

Typical Industries

- Construction
- Engineering
- Logistics
- Municipal Services
- Transport

Suitable Applications

- Assembly
- Final Fix
- Light Engineering
- Precision Operations

CERTIFICATION









SKYTEC SKYTEC ECO COPPER™

PRODUCT INFORMATION

MATERIALS	LINER:	15 gauge 90% recycled polyester (rPET)
	COATING:	Natural Latex
COLOUR	Green	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKG00051ED SKG00051EF SKG00051EH SKG00051EJ SKG00051EL	10 pairs per paper wrap 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove. Not suitable for thermal up to 100C, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

CLASSIFICATION FOR CUT RESISTANCE				
Measured breakthrough time	Permeation performance index (grams)			
A1	≥ 200			
A2	≥ 500			
A3	≥ 1000			
A4	≥ 1500			
A5	≥ 2200			
A6	≥ 3000			
A7	≥ 4000			
A8	≥ 5000			
A9	> 6000			



Burning Behaviour

HEAT AND FIRE EN 407

PERFORMANCE LEVELS 0-4 0-4 0-4 0-4 0-4 0-4 Resistance to Large Splashes of Molten Metal Resistance to Small Drops Of Molten Metal Radiant Heat Resistance Convective Heat Resistance Contact Heat Resistance

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 T: F: +971 4 882 9963

GLOBUS AMERICAS

www.globusgroup.com

E: americas@globusgroup.com



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-ECO-COPPER-0123 2