

### FULLY COATED NITRILE GLOVE WITH RECYCLED POLYESTER LINER

Fully coated nitrile with a nitrile foam palm and 100% rPET liner. Excellent grip in wet and oily conditions as well as oil and water submersion.

#### **FEATURES**

- ➤ A flexible, robust glove with 100% recycled polyester (rPET) liner
- Protects the hand from water, oils, hydrocarbons, grease and abrasion, with optimal long lasting grip
- Touchscreen capabilities to allow usage with screen devices
- Contact heat protection up to 100°C for a short period (15 sec max)
- > RCS (Recycled Claim Standard) certified
- > Designed for easy movement and continuous wear
- > Close-fitting liner for a comfortable wearing experience
- > Elasticated wrist provides a secure fit
- ➤ 1 pair = 2 500ml (PET) plastic bottles, recycled















#### **SUITABLE FOR**

#### **Typical Industries**

- Aerospace
- Automotive
- Construction
- Engineering
- Manufacturing
- Oil and Gas

## **Suitable Applications**

- Concreting
- Handling Oily Components
- Maintenance
- Oil Submersion
- Painting
- Wet Work

## CERTIFICATION



See overleaf for explanation

# ANSI ANSI ANSI ANSI 2







#### **PRODUCT INFORMATION**

MATERIALS	LINER:	15 gauge 100% recycled polyester (rPET)		
	COATING:	Foam nitrile over nitrile		
COLOUR	Blue/black			
LENGTH (mm)	250 (size dependent)			
CUFF STYLE	Elasticated knit wrist			

#### **ORDERING DETAILS**

SIZE	CODE	PACKAGING
6/XS 7/S 8/M 9/L 10/XL 11/XXL	SKG00047BB SKG00047BD SKG00047BF SKG00047BH SKG00047BJ SKG00047BL	10 pairs per paper wrap 120 pairs per case

#### **RECOMMENDATIONS FOR USE**

- USE: General handling glove. Not suitable for thermal up to 100C, electrical or chemical protection. Do not use near moving machines if there is a risk
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

#### **CERTIFICATION LEGENDS**



\*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



PERFORMANCE LEVELS 0-4 0-4 0-4 0-4 0-4 Resistance to Large Splashes of Molten Metal Resistance to Small Drops Of Molten Metal Radiant Heat Resistance Convective Heat Resistance Contact Heat Resistance Burning Behaviour

ANSI/ISEA PUNCTURE RESISTANCE						
ANSI Puncture Level	Puncture Resistance (newtons)					
1	10-19					
2	20-59					
3	60-99					
4	100-149					
5	150+					
	and the second second second					

Puncture Resistance (ANSI/ISEA 105): Puncture resistance that it takes, exerted from a probe, to puncture the fabric

ANSI/ISEA 105-2016 ABRASION RATING CHART								
Abrasion Level Rating	0	1	2	3	4	5	6	
Gram Load	500	500	500	500	1000	1000	1000	
Abrasion Cycles to Fail	<100	≥100	≥500	≥1,000	≥3,000	≥10,000	≥20,000	

# GLOBUS

**EUROPE** 

#### www.globusgroup.com

**E:** sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

#### **MIDDLE EAST AND AFRICA**

#### www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963

# **GLOBUS AMERICAS**

www.globusgroup.com

E: americas@globusgroup.com

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES Globus Americas LLC, 45 Rockefeller Plaza, Suite 2000, New York City, New York, 10111, USA

© 2023 Globus (Shetland) Ltd | SKY-DATA-ECO-CHROME-0623 1