

EVOLite[®] SKYWORKER MICRO PEAK - WHEEL RATCHET

TECHNICAL SPECIFICATION

PRODUCT CODE: AJS260-000-100

THE HEIGHT SAFETY SPECIALIST HELMET CONFORMING TO EN12492 AND THE IMPACT TEST OF EN397

HEAD PROTECTION

INSTRUCTIONS FOR USE

Fit helmet on head and fasten strap to ensure fit

For adequate protection this helmet must be worn with peak facing forward

Ensure the helmet is adjusted to the size of the user's head

WEBBING HARNESS:

HDPE Strap & Webbing Clips with Polyester Webbing Straps

CHAMLON[™] SWEATBAND:

Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested

4 POINT CHINSTRAP:

Four-point 'X-over' Chinstrap and adjustable harness system comes with a quick release buckle and is made from durable yet soft material, for a comfortable fit

SHELL:

High strength engineering grade ABS



REVOLUTION

WHEEL RATCHET:

The Revolution[®] Wheel Ratchet is the new easy to use wheel ratchet adjustment system to create a firm comfort fit with added security



LINER:

Polystyrene (EPS)

CLEANING & MAINTENANCE

The unit may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY

Conforms to EN12492 Mountaineering standard

Conforms to EN397 Shock Absorption and Penetration

Conforms to EN50365 Electrical Insulation Test

Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective Kit

Meets optional Molten Metal Splash performance

Meets optional very low temperature performance (-40°C)

Meets Lateral Deformation requirements

EC Certificate Number 601644, issued by BSi Product Certification

Company personalisation available by printing



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
EXPORT@JSP.CO.UK
TEL: +44 (0)1993 826050



EVOLite[®] SKYWORKER MICRO PEAK - WHEEL RATCHET

PRODUCT CODE: AJS260-000-100

THE HEIGHT SAFETY SPECIALIST HELMET CONFORMING TO EN12492 AND THE IMPACT TEST OF EN397

TECHNICAL SPECIFICATION

HEAD PROTECTION

HELMET FEATURES

EN STANDARD	EN12492 EN397 EN50365	Yes Shock & Penetration Yes
PERFORMANCE	Impact Resistance Lateral Deformation Electrical Insulation	Yes 50 Joules Crown 25 Joules Side Yes Yes: EN50365 1000V
TEMPERATURE RESISTANCE	Molten Metal (MM) +50°C -40°C	Yes Yes Yes
SHELL MATERIAL	ABS Recyclable UV Stabilised	Yes Yes Yes
CHINSTRAP	4 pts	Yes
HARNESS MATERIAL	HDPE LDPE Textile	Yes Yes Yes
HARNESS SYSTEM	JSP 3D Wheel Ratchet	Yes Yes
OPTIONS	Universal Accesories Reflective CR2 Integrated Eyewear	Yes Yes No
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

DIMENSIONS OF INNER PACKAGING

Quantity: 1

Weight: 565g (Approx.)



HEIGHT:
157mm

WIDTH:
220mm

LENGTH:
260mm

DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 395g (Approx.)

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer



MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK

UKSALES@JSP.CO.UK
EXPORT@JSP.CO.UK
TEL: +44 (0)1993 826050

