

TECHNICAL SPECIFICATION



PressToCheck™ ABEK1 P3 Filters

Pack of 2 / BMN750-000-600



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4713 ABEK1P3 multi- gas / vapour + dust replacement encapsulated filters, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN750-000-600)

SAFETY STANDARDS

EN 14387



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 22 Jan 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
ABEK1P3

Usage
R (Reusable)



Activated Carbon Filter
Yes

Maximum Total Inward Leakage (TIL)
2% when fitted to Force8 Half Mask

Nominal Protection Factor
1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor
20 When Fitted To A Force10 Full Face Mask

Latex free
Yes

Filter Material
Pleated media & activated carbon

Filter Shelf Life
10 Years



Product Weight
245g Per Pair



Filter Type
Organic, Inorganic, Acidic, Amonia Vapours and Particulate



(D) Resistance to dust clogging
Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency
99.95% For P3 Rated

Nominal Protection Factor
12 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor
10 When Fitted To A Force8 Half Mask



Type
Press to Check Technology

Metal Free
Yes

Filter Casing Material
ABS



BSI Kitemark
Yes

Maximum Total Inward Leakage (TIL)
0.05% when fitted to a Force10 Full Face Mask




FEATURES



Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

VIDEOS

-  youtu.be/1Y9G8E9kEXQ
-  youtu.be/Ecyu_ftPPX4
-  youtu.be/-oUSyP9_NsA

DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-force-press-to-check-filter-f-4713.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 22 Jan 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

